

Description

Fastener Length: 3/4", Thread: 1/2-13, Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C08LL5
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-416-5236
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS1352C08LL5 Specifications

Thread Class:	3a
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Locking Feature:	Strip Locking Feature
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.3750 Inches Minimum And 0.3790 Inches Maximum
Thread Quantity Per Inch:	13
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Thread Series Designator:	Unrc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LL5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.