

Description

Fastener Length: 1/2", Thread: 8-32, Head Width: 9/64", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C08LL8
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-760-6904
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1352C08LL8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.140 Inches Minimum And 0.142 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
Material Document And Classification:	Astm A493 Assn Std All Material Responses Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C08LL8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.