

## P/N NAS1352C3-20

## **Description**

Fastener Length: 1-1/4", Thread: 10-24, Head Width: 5/32", Thread Length: 1-5/32

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1352C320

Minimum Qty (MOQ): 25

NSN: 5305-01-028-8146

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352C3-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.127 Inches Minimum And 1.167 Inches Maximum
Fastener Length:	1.210 Inches Minimum And 1.250 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.1562 Inches Minimum And 0.1587 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	70000 Pounds Per Square Inch
Hardness Rating:	74.0 Rockwell B Minimum Overall
Minimum Yield Strength:	26000 Pounds Per Square Inch
Material:	Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or X-7 Astm A493 Assn Std 6th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20</a> and selecting the quantity you