

P/N NAS1352C3-20

Description

Fastener Length: 1-1/4", Thread: 10-24, Head Width: 5/32", Thread Length: 1-5/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352C320

Minimum Qty (MOQ): 25

NSN: 5305-01-028-8146

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1352C3-20 Specifications

3a
Right-hand
1.127 Inches Minimum And 1.167 Inches Maximum
1.210 Inches Minimum And 1.250 Inches Maximum
Flat Chamfer
0.303 Inches Minimum And 0.313 Inches Maximum
0.185 Inches Minimum And 0.190 Inches Maximum
Hexagon
0.190 Inches
0.1562 Inches Minimum And 0.1587 Inches Maximum
24
70000 Pounds Per Square Inch
74.0 Rockwell B Minimum Overall
26000 Pounds Per Square Inch
Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall
66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or X-7 Astm A493 Assn Std 6th Material Response Overall
Passivate Overall
Qq-p-35 Fed Spec Single Treatment Response Overall
Unrc
80205-nas1352 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C3-20 and selecting the quantity you