

Description

Fastener Length: 5/8", Thread: 1/4-20, Head Width: 3/16", Thread Length: 5/8", NAS1352 series screw


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS16995-49](#) [NAS1352C410](#)

SKU / Model:	NAS1352C410
Minimum Qty (MOQ):	25
NSN:	5305-01-121-2719
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1352C4-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.495 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.595 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.187 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C4-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.