

## Description

length: 1-1/4", thread: 1/4-28, hex socket head, corrosion resistant steel, NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

NAS1352C420 MS16995-53

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1352C420                               |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5305-00-497-5287                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1352C4-20 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 1.000 Inches Minimum   |
| <b>Fastener Length:</b>                               | 1.210 Inches Minimum And 1.250 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.375 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.244 Inches Minimum And 0.250 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Width Across Flats:</b>                            | 0.188 Inches Minimum And 0.190 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 20   |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall  |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch   |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 316 Overall Or Steel Comp Xm-7 Overall  |
| <b>Material Document And Classification:</b>          | 66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Assn Std 6th Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unrc   |
| <b>Nondefinitive Spec/std Data:</b>                   | 6 Type   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C4-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.