

Description

Fastener Length: 1-3/4", Thread: 1/4-20, Head Width: 3/16", Thread Length: 1-

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1352C428
Minimum Qty (MOQ):	20
NSN:	5305-01-028-6463
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1352C4-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum
Fastener Length:	1.710 Inches Minimum And 1.750 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or 66 Fed Std 2nd Material Response Overall Or 66 Fed Std 3rd Material Response Overall Or 66 Fed Std 4th Material Response Overall Or 66 Fed Std 5th Material Response Overall Or Astm A493 Type Xm-7 Assn Std 6th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C4-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.