

Description

Fastener Length: 3/4", Hole Diameter: 3/64", Thread: 1/4-20, Head Width: 3/16", Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1352C4H12 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-108-0650 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1352C4H12 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.620 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.720 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.365 Inches Minimum And 0.375 Inches Maximum |
| Head Height: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.188 Inches Minimum And 0.190 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Hole Configuration Style: | Round Internal Hexagon |
| Material: | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/Industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C4H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.