

P/N NAS1352C6-48

Description

Fastener Length: 2-63/64", Thread: 3/8-16, Head Width: 1/4", Thread Length: 1-1/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352C648

Minimum Qty (MOQ):

NSN: 5305-01-425-3048

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









^{*} See page 2 for technical characteristics

P/N NAS1352C6-48 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Nominal
Fastener Length:	2.940 Inches Minimum And 3.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.550 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.368 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.2500 Inches Minimum And 0.2530 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp 384 Overall Or Steel Comp Xm-7 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C6-48 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.