

## Description

Fastener Length: 1-1/2", Thread: 1/2-13, Head Width: 3/8", Thread Length: 1-1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1352C824                               |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 5305-01-173-5042                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1352C8-24 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 1.346 Inches Minimum And 1.500 Inches Maximum   |
| <b>Fastener Length:</b>                               | 1.440 Inches Minimum And 1.500 Inches Maximum   |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.735 Inches Minimum And 0.750 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.492 Inches Minimum And 0.500 Inches Maximum   |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.500 Inches  |
| <b>Width Across Flats:</b>                            | 0.375 Inches Minimum And 0.379 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 13  |
| <b>Minimum Tensile Strength:</b>                      | 80000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 80.0 Rockwell B Minimum Overall   |
| <b>Minimum Yield Strength:</b>                        | 30000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall Or Steel Comp Xm-7 Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unrc  |
| <b>Specification/standard Data:</b>                   | 80205-nas1352 Professional/industrial Association Standard  |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352C8-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.