

Description

Fastener Length: 15/64", Thread: 1-64, Head Width: 1/16", Thread Length: 13/64", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1352N014 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-01-326-5747 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1352N01-4 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.220 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.112 Inches Minimum And 0.118 Inches Maximum |
| Head Height: | 0.070 Inches Minimum And 0.073 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.073 Inches |
| Width Across Flats: | 0.062 Inches Minimum And 0.063 Inches Maximum |
| Thread Quantity Per Inch: | 64 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N01-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.