

Description

Fastener Length: 1-", Thread: 2-56, Head Width: 5/64", Thread Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1352N0216 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-351-3516 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



P/N NAS1352N02-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.134 Inches Minimum And 0.140 Inches Maximum |
| Head Height: | 0.083 Inches Minimum And 0.086 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.086 Inches |
| Width Across Flats: | 0.0781 Inches Minimum And 0.0791 Inches Maximum |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 120000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/Industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.