

## P/N NAS1352N02-2

### **Description**

NAS1352N02-2 Socket head Cap Screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1352N022

Minimum Qty (MOQ): 25

NSN: 5305-01-181-0804

ECCN: EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352N02-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.059 Inches Minimum And 0.125 Inches Maximum
Fastener Length:	0.095 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.0781 Inches Minimum And 0.0791 Inches Maximum
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-2">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.