

Description

NAS1352N02-2 Socket head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1352N022
Minimum Qty (MOQ):	25
NSN:	5305-01-181-0804
ECCN:	EAR99

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1352N02-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.059 Inches Minimum And 0.125 Inches Maximum
Fastener Length:	0.095 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.086 Inches
Width Across Flats:	0.0781 Inches Minimum And 0.0791 Inches Maximum
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.