

P/N NAS1352N02-2

Military-Fasteners.com

#### Description

NAS1352N02-2 Socket head Cap Screw

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1352N022
Minimum Qty (MOQ):	25
NSN:	5305-01-181-0804
ECCN:	EAR99



# P/N NAS1352N02-2 Specifications

Thread Class:	3a	
Thread Direction:	Right-hand	
Thread Length:	0.059 Inches Minimum And 0.125 Inches Maximum	
Fastener Length:	0.095 Inches Minimum And 0.125 Inches Maximum	
Head Style:	Flat Chamfer	
Head Diameter:	0.134 Inches Minimum And 0.140 Inches Maximum	
Head Height:	0.083 Inches Minimum And 0.086 Inches Maximum	
Internal Drive Style:	Hexagon	
Nominal Thread Diameter:	0.086 Inches	
Width Across Flats:	0.0781 Inches Minimum And 0.0791 Inches Maximum	
Thread Quantity Per Inch:	56	
Minimum Tensile Strength:	160000 Pounds Per Square Inch	
Material:	Iron Alloy 660 Overall	
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall	
Surface Treatment:	Passivate Overall	
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall	
Thread Series Designator:	Unrc	
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard	

## How to Order

Order this socket head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.