

## P/N NAS1352N02-7

### **Description**

NAS1352N02-7 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1352N027

Minimum Qty (MOQ): 25

NSN: 5305-01-246-8442

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352N02-7 Specifications

| Thread Class:                                  | 3a                                                                                                     |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| Thread Direction:                              | Right-hand                                                                                             |
| Thread Length:                                 | 0.372 Inches Minimum And 0.438 Inches Maximum                                                          |
| Fastener Length:                               | 0.408 Inches Minimum And 0.438 Inches Maximum                                                          |
| Head Style:                                    | Flat Chamfer                                                                                           |
| Head Diameter:                                 | 0.134 Inches Minimum And 0.140 Inches Maximum                                                          |
| Head Height:                                   | 0.083 Inches Minimum And 0.086 Inches Maximum                                                          |
| Internal Drive Style:                          | Hexagon                                                                                                |
| Nominal Thread Diameter:                       | 0.086 Inches                                                                                           |
| Width Across Flats:                            | 0.078 Inches Minimum And 0.079 Inches Maximum                                                          |
| Thread Quantity Per Inch:                      | 56                                                                                                     |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch                                                                          |
| Material:                                      | Iron Alloy 660 Overall                                                                                 |
| Material Document And Classification:          | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Passivate Overall                                                                                      |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall                                                     |
| Thread Series Designator:                      | Unrc                                                                                                   |
| Specification/standard Data:                   | 80205-nas1352 Professional/industrial Association Standard                                             |

## **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-7">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N02-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.