

**Description**

NAS1352N04-20 Machine Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1352N0420
Minimum Qty (MOQ):	10
NSN:	5305-01-375-7350
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1352N04-20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Minimum
<b>Fastener Length:</b>	1.210 Inches Minimum And 1.250 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.176 Inches Minimum And 0.183 Inches Maximum
<b>Head Height:</b>	0.108 Inches Minimum And 0.112 Inches Maximum
<b>Width Between Flats:</b>	0.0937 Inches Minimum And 0.0952 Inches Maximum
<b>Internal Drive Style:</b>	Err-090
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.0937 Inches Minimum And 0.0952 Inches Maximum
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Or Ms 5737 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unrc
<b>Specification/standard Data:</b>	80205-nas1352 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1352N04-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.