

Description

NAS1352N04-26 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1352N0426 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-247-3699 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N NAS1352N04-26 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum |
| Fastener Length: | 1.585 Inches Minimum And 1.625 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.176 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.108 Inches Minimum And 0.112 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.093 Inches Minimum And 0.095 Inches Maximum |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N04-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.