

**Description**

NAS1352N04H12 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1352N04H12
Minimum Qty (MOQ):	5
NSN:	5305-01-360-7867
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1352N04H12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Maximum
<b>Fastener Length:</b>	0.720 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.176 Inches Minimum And 0.183 Inches Maximum
<b>Head Height:</b>	0.108 Inches Minimum And 0.112 Inches Maximum
<b>Hole Diameter:</b>	0.033 Inches Minimum And 0.039 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.0937 Inches Minimum And 0.0952 Inches Maximum
<b>Hole Quantity:</b>	2
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Round Internal Hexagon
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrc
<b>Specification/standard Data:</b>	80205-nas1352 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N04H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.