

Description

flat head, drilled

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1352N04H8
Minimum Qty (MOQ):	10
NSN:	5305-01-539-9351
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS1352N04H8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.176 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.108 Inches Minimum And 0.112 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	4810-01-461-1917
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.094 Inches Nominal
Thread Quantity Per Inch:	40
Special Features:	Heat-resistance Steel W/drilled Holes In The Head
Material:	Steel Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unrc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N04H8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.