

## P/N NAS1352N06-12B

### **Description**

Fastener Length: 3/4", Thread: 6-32, Head Width: 3/32", Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1352N0612B

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-585-0554

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352N06-12B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	0.750 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	F-16 Aircraft
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Nominal
Thread Quantity Per Inch:	32
Color:	Black Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Oxide Overall
Thread Series Designator:	Unc

## **How to Order**

Order this socket head screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-12B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nas18">https://military-fasteners.com/screws/nas18</a> and selecting the property of t