

P/N NAS1352N06-8B

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 3/4", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352N068B

Minimum Qty (MOQ):

NSN: 5305-01-467-6372

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









^{*} See page 2 for technical characteristics

P/N NAS1352N06-8B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	0.500 Inches Nominal
End Item Identification:	1520-01-135-8250
Nominal Thread Diameter:	0.1380 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1458 Pounds Per Square Inch
Special Features:	The Body Diameter Of The Item Is 0.1329 In. Min., 0.138 In.max.; Head Diameter Is 0.218 In. Min., 0.226 In Max.; Head Height Is 0.134 Inmin., 0.138 In. Max.
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-c-13924, Class3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unrc

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-8B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-8B and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-8B and