

**Description**

Fastener Length: 1/2", Thread: 6-32, Thread Length: 3/4", NAS1352 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1352N068B
Minimum Qty (MOQ):	10
NSN:	5305-01-467-6372
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS1352N06-8B Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Nominal
<b>Fastener Length:</b>	0.500 Inches Nominal
<b>End Item Identification:</b>	1520-01-135-8250
<b>Nominal Thread Diameter:</b>	0.1380 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	1458 Pounds Per Square Inch
<b>Special Features:</b>	The Body Diameter Of The Item Is 0.1329 In. Min., 0.138 In.max.; Head Diameter Is 0.218 In. Min., 0.226 In Max.; Head Height Is 0.134 Inmin., 0.138 In. Max.
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Oxide Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-13924, Class3 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrc

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06-8B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.