

Description

Socket Head Cap Screw part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1352N06H10 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-144-3905 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1352N06H10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.533 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.595 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.134 Inches Minimum And 0.138 Inches Maximum |
| Hole Diameter: | 0.033 Inches Minimum And 0.039 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.109 Inches Minimum And 0.111 Inches Maximum |
| Hole Quantity: | 2 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Round Internal Hexagon |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.