

P/N NAS1352N06H16

Description

Fastener Length: 0-63/64", Hole Diameter: 1/32", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352N06H16

Minimum Qty (MOQ): 10

NSN: 5305-01-455-4378

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









^{*} See page 2 for technical characteristics

P/N NAS1352N06H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Hole Diameter:	0.033 Inches Minimum And 0.039 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round Internal Hexagon
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.