



★ FASTENERS

Military-Fasteners.com

P/N NAS1352N06LB-8

Description

NAS1352N06LB-8 Socket Head Cap Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS1352N06LB8 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-392-5070 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N NAS1352N06LB-8 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Nominal |
| Fastener Length: | 0.470 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.134 Inches Minimum And 0.138 Inches Maximum |
| Locking Feature: | Patch Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.1094 Inches Minimum And 0.1111 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unrc |
| Specification/standard Data: | 80205-nas1352 Professional/Industrial Association Standard |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06LB-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.