

P/N NAS1352N06LE6

Description

Fastener Length: 3/8", Thread: 6-32, Head Width: 7/64", Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352N06LE6

Minimum Qty (MOQ): 25 EA

NSN: 5305-01-455-9610

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1352N06LE6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Fastener And 42.0 Rockwell C Maximum Fastener
Minimum Yield Strength:	120000 Pounds Per Square Inch
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Fastener Or Ams 5737 Assn Std Single Material Response Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N06LE6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.