

**Description**

Fastener Length: 5/8", Thread: 8-32, Head Width: 9/64", Thread Length: 5/8", NAS1352 series screw


\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS1352N0810](#)

|                         |                                  |
|-------------------------|----------------------------------|
| SKU / Model:            | NAS1352N0810                     |
| Minimum Qty (MOQ):      | 25                               |
| NSN:                    | 5305-01-071-7134                 |
| Schedule B:             | 7318.15.6080                     |
| ECCN:                   | EAR99                            |
| National Motor Freight: | 096660, Screws Noi Silver Plated |



\* See page 2 for technical characteristics

## P/N NAS1352N08-10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.533 Inches Minimum And 0.625 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.595 Inches Minimum And 0.625 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.262 Inches Minimum And 0.270 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.159 Inches Minimum And 0.164 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches   |
| <b>Width Across Flats:</b>                            | 0.141 Inches Minimum And 0.143 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Silver Overall   |
| <b>Surface Treatment Document And Classification:</b> | Ams 2411 Assn Std Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unrc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1352 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.