

P/N NAS1352N08-11

Description

Fastener Length: 11/16", Thread: 8-32, Head Width: 9/64", Thread Length: 11/16

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1352N0811

Minimum Qty (MOQ): 10

NSN: 5305-01-246-5768

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1352N08-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.595 Inches Minimum And 0.687 Inches Maximum
Fastener Length:	0.657 Inches Minimum And 0.687 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08-11 and