

Description

Fastener Length: 3/8", Thread: 8-32, Head Width: 9/64", Thread Length: 3/8", NAS1352 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[NAS1352N086](#)

SKU / Model:	NAS1352N086
Minimum Qty (MOQ):	25
NSN:	5305-01-107-3546
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1352N08-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.283 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.