

# P/N NAS1352N08H16

## **Description**

Fastener Length: 1", Hole Diameter: 3/64", Thread: 8-32, Head Width: 9/64", Thread Length: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: NAS1352N08H16

Minimum Qty (MOQ):

NSN: 5305-01-501-6315

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352N08H16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Nominal
Fastener Length:	1.000 Inches Nominal
Head Style:	Pan No. 2
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Hole Diameter:	0.044 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	Fuselage
Nominal Thread Diameter:	0.1640 Inches
Width Across Flats:	0.141 Inches Nominal
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Round Internal Hexagon
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1352 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08H16">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N08H16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.