

# P/N NAS1352N4-14

## **Description**

NAS1352N4-14 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: NAS1352N414

Minimum Qty (MOQ): 10

NSN: 5305-01-379-5144

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1352N4-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Maximum
Fastener Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.1875 Inches Minimum And 0.1900 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unrc
Specification/standard Data:	80205-nas1531 Professional/industrial Association Standard

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N4-14">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N4-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.