

**Description**

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 1/4-20, Head Width: 3/16", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS1352N4H10                  |
| Minimum Qty (MOQ):      | 1 EA                          |
| NSN:                    | 5305-01-512-5607              |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS1352N4H10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.495 Inches Minimum And 0.625 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.595 Inches Minimum And 0.625 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.375 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.244 Inches Minimum And 0.250 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.044 Inches Minimum And 0.050 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>End Item Identification:</b>                       | Gas Gen Assy   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Width Across Flats:</b>                            | 0.187 Inches Minimum And 0.190 Inches Maximum  |
| <b>Hole Quantity:</b>                                 | 6  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Thread Quantity Per Inch:</b>                      | 20   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>                      | Round Internal Hexagon   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unrc   |

## How to Order

Order this socket head screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N4H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.