

## Description

NAS1352N5-24 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1352N524
Minimum Qty (MOQ):	5
NSN:	5305-01-252-9154
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1352N5-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.125 Inches Minimum And 1.500 Inches Maximum
<b>Fastener Length:</b>	1.470 Inches Minimum And 1.500 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.457 Inches Minimum And 0.469 Inches Maximum
<b>Head Height:</b>	0.306 Inches Minimum And 0.312 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.250 Inches Minimum And 0.253 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unrc
<b>Specification/standard Data:</b>	80205-nas1352 Professional/industrial Association Standard

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N5-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.