

Description

NAS1352N6-36 Socket Head Cap Screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS1352N636                   |
| Minimum Qty (MOQ):      | 1                             |
| NSN:                    | 5305-01-389-6328              |
| ECCN:                   | EAR99                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



\* See page 2 for technical characteristics

## P/N NAS1352N6-36 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 1.250 Inches Minimum   |
| <b>Fastener Length:</b>                               | 2.210 Inches Minimum And 2.250 Inches Maximum  |
| <b>Head Style:</b>                                    | Flat Chamfer   |
| <b>Head Diameter:</b>                                 | 0.550 Inches Minimum And 0.562 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.368 Inches Minimum And 0.375 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches   |
| <b>Width Across Flats:</b>                            | 0.3125 Inches Minimum And 0.3160 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 16   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 33.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall                                      |
| <b>iii Part Name Assigned By Controlling Agency:</b>  | Navy Special Project   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unrc   |
| <b>Specification/standard Data:</b>                   | 80204-nas1352 Professional/industrial Association Standard   |

## How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS1352N6-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.