

**P/N NAS1354DS7S15D** 

Military-Fasteners.com

#### Description

NAS1354 series pin

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS1354DS7S15D
Minimum Qty (MOQ):	1
NSN:	5315-00-079-9235
Schedule B:	7318.29.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



# P/N NAS1354DS7S15D Specifications

Head Diameter:	0.750 Inches Maximum
Shank Diameter:	0.2470 Inches Minimum And 0.2495 Inches Maximum
Ring Handle Diameter:	1.220 Inches Nominal
Detent Quantity:	2
Actuation Method:	Push Button
Grip Length:	1.500 Inches Minimum And 1.520 Inches Maximum
Actuation Type:	Pull And Push
Features Provided:	Drive Out Feature
Hardness Rating:	36.0 Rockwell C Minimum Shank And 40.0 Rockwell C Maximum Shank
Hardness Rating:	36.0 Rockwell C Minimum Spindle And 40.0 Rockwell C Maximum Spindle
Hardness Rating:	54.0 Rockwell C Minimum Detent And 64.0 Rockwell C Maximum Detent
Shoulder To Head End Distance:	1.730 Inches Maximum
Pin Attachment Type:	Hook Or Ring
Detent To Tapered End Distance:	0.410 Inches Maximum
Material:	Steel Comp 4130 Shank Or Steel Comp 4135 Shank
Material:	Steel Comp 4130 Spindle
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Shank Or Mil-t-6736 Mil Spec 1st Material Response Shank Or Mil-t-6735 Mil Spec 2nd Material Response Shank
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Spindle
Surface Treatment:	Cadmium Shank And Chromate Shank
Surface Treatment:	Cadmium Spindle And Chromate Spindle
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Shank
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Spindle
Style Designator:	Ring Handle
Specification/standard Data:	80205-nas1354 Professional/industrial Association Standard

## How to Order

Order this quick release pin from our inventory online by visiting <u>https://military-fasteners.com/pins/quick+release+pins/NAS1354DS7S15D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.