

Description

Thread Size: 1/4", Thread Length: 1/4",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS51831CA202L](#)

| | |
|-------------------------|-----------------------------|
| SKU / Model: | NAS1395CA4L |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5325-01-113-0927 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



* See page 2 for technical characteristics

P/N NAS1395CA4L Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Thread Length: | 0.305 Inches Nominal |
| Length: | 0.360 Inches Minimum And 0.390 Inches Maximum |
| Insert Size: | 7/16-14 Unc 2a |
| Internal Thread Relief Depth: | 0.060 Inches Minimum And 0.080 Inches Maximum |
| Full Internal Thread Length: | 0.280 Inches Minimum And 0.330 Inches Maximum |
| Features Provided: | Individually Keyed |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Special Features: | Dry Film Lubricant. Has Internal Thread Lock |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 5734 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | Keylock |
| Thread Series Designator: | Unjf |

How to Order

Order this screw thread insert from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/NAS1395CA4L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.