

Description

Cr Lock Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1398B8A6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-450-4076 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398B8A6 Specifications

| | |
|-----------------------------|---|
| Fastener Length: | 0.573 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.250 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Material: | Aluminum Alloy 5056 Overall |
| Surface Treatment: | Anodize Overall |

How to Order

Order this cr lock rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398B8A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.