

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1398C3A2 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-597-3083 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398C3A2 Specifications

| | |
|-----------------------------|---|
| Head Style: | Universal |
| Head Height: | 0.040 Inches Nominal |
| Shank Diameter: | 0.094 Inches Nominal |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.187 Inches Nominal |
| Grip Length: | 0.063 Inches Minimum And 0.125 Inches Maximum |
| Special Features: | Letter "a" In Part Number Represents Rivet With Full Serrated Spindle |
| Material: | Iron Alloy 660 Mechanical Lock |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Surface Treatment: | Passivate Sleeve |
| Surface Treatment: | Passivate Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C3A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.