

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398C3A2
Minimum Qty (MOQ):	100
NSN:	5320-01-597-3083
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1398C3A2 Specifications

Head Style:	Universal
Head Height:	0.040 Inches Nominal
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.187 Inches Nominal
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Special Features:	Letter "a" In Part Number Represents Rivet With Full Serrated Spindle
Material:	Iron Alloy 660 Mechanical Lock
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Surface Treatment:	Passivate Sleeve
Surface Treatment:	Passivate Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C3A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.