

Description

NAS1398C4-5 Blind Rivet, Alternate CR2663-4-05

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CR2663-4-05](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS1398C45 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-526-2820 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1398C4-5 Specifications

| | |
|--|--|
| Fastener Length: | 0.448 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.251 Inches Minimum And 0.312 Inches Maximum |
| Shear Strength: | 970 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring |
| Material Document And Classification: | Qq-n-281 Cl A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Cl B Fed Spec 2nd Material Response Locking Ring |
| Specification/standard Data: | 80205-nas1398 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.