

Description

NAS1398C4-5 Blind Rivet, Alternate CR2663-4-05

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CR2663-4-05](#)

SKU / Model:	NAS1398C45
Minimum Qty (MOQ):	100
NSN:	5320-00-526-2820
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1398C4-5 Specifications

Fastener Length:	0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Shear Strength:	970 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
Material Document And Classification:	Qq-n-281 Cl A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Cl B Fed Spec 2nd Material Response Locking Ring
Specification/standard Data:	80205-nas1398 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.