

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1398C4A6
Minimum Qty (MOQ):	10
NSN:	5320-01-047-6336
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1398C4A6 Specifications

<b>Fastener Length:</b>	0.510 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Minimum And 0.064 Inches Maximum
<b>Shank Diameter:</b>	0.125 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Nickel Alloy 400 Locking Ring Or Nickel Alloy R-405 Locking Ring
<b>Material Document And Classification:</b>	Qq-n-281 Cl A Fed Spec 1st Material Response Locking Ring Or Qq-n-281 Cl B Fed Spec 2nd Material Response Locking Ring
<b>Specification/standard Data:</b>	80205-nas1398 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C4A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.