

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398C4AB1
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-500-9647
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1398C4AB1 Specifications

Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shoulder Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shoulder Length:	0.198 Inches Nominal
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F119 Engine
Grip Length:	0.025 Inches Minimum And 0.062 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet-blind, Protruding Head, Locked Spindle
Material:	Steel Corrosion Resisting Sleeve
Material Document And Classification:	Ams5732 Assn Std 1st Material Response Sleeve Or Ams5737 Assn Std 1st Material Response Sleeve
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Ams-qq-p-35 Fed Spec 1st Treatment Response Sleeve

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C4AB1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.