

P/N NAS1398C4AB7

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1398C4AB7

Minimum Qty (MOQ): 15 EA

NSN: 5320-01-519-2358

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N NAS1398C4AB7 Specifications

| Fastener Length: | 0.573 Inches Maximum |
|----------------------|-----------------------------------------------|
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.250 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| Grip Length: | 0.376 Inches Minimum And 0.437 Inches Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Iron Alloy 660 Stem |
| Material: | Nickel Alloy 400 Locking Ring |
| Surface Treatment: | Passivate Sleeve |
| Surface Treatment: | Passivate Stem |

How to Order

Order this cr max rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1398C4AB7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1398C4AB7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1398C4AB7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/NAS1398C4AB7 and selecting the quantity you want https://military-fasteners.com/rivets/NAS1398C4AB7 and selecting the your cart you can check out https://military-fasteners.com/rivets/NAS1398C4AB7 and selecting the your cart you can check yo