

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398C4AB7
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-519-2358
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1398C4AB7 Specifications

Fastener Length:	0.573 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Nominal
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
Grip Length:	0.376 Inches Minimum And 0.437 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring
Surface Treatment:	Passivate Sleeve
Surface Treatment:	Passivate Stem

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C4AB7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.