

Description

Blind Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398C5AB1
Minimum Qty (MOQ):	100
NSN:	5320-01-504-6372
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1398C5AB1 Specifications

Fastener Length:	0.201 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	F119 Engine
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet
Material:	Iron Alloy 660 Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Locking Ring
Surface Treatment:	Passivate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Locking Ring
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Ams-qq-p-35 Assn Std Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C5AB1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.