

Description

Fastener Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1398C6A2
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-296-3040
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1398C6A2 Specifications

Fastener Length:	0.287 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Expansion Device:	Serrated Stem-type W
End Item Identification:	Wsd: Aircraft, Viking S-3b; Aircraft, B-2 Bomber (atb); Aircraft, Harrier Av-8b; Aircraft, Eagle F-15; Support Equipment (se), B-2 Bomber; Engine, F119-pw-100 (f-22 Raptor); F/a-18e/f Hornet Aircraft; Aircraft, Hornet F/a-18; Helicopter, Uh-60a/uh-60d
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Nickel Alloy Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Locking Ring
Specification/standard Data:	80205-nas1398 Professional/Industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C6A2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.