

## **P/N NAS1398C6AB6**

### **Description**

Blind Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1398C6AB6

Minimum Qty (MOQ): 10 EA

NSN: 5320-01-574-7194

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1398C6AB6 Specifications

Fastener Length:	0.537 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Nominal
Shank Diameter:	0.187 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.375 Inches Nominal
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material:	Nickel Alloy 400 Locking Ring

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1398C6AB6">https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1398C6AB6">https://military-fasteners.com/rivets/NAS1398C6AB6</a> and selecting the quantity you want then click "add to cart".