

Description

Cr Max Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1398C6AB9
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-561-1720
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1398C6AB9 Specifications

Fastener Length:	0.787 Inches Maximum
Head Style:	Countersunk W/protruding Stud
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.190 Inches Nominal
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	8.0 Degrees Nominal
Material:	Nickel Alloy Locking Ring
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Surface Treatment:	Passivate Sleeve

How to Order

Order this cr max rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1398C6AB9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.